

Webhooks

Introduction

You can create webhooks in Extend.


The webhook will make a call based on the events (triggers) that you define on the webhook.

På denna sida:


- [Introduction](#)
- [Add / edit Webhooks](#)
- [Example](#)
- [Signing](#)

Add / edit Webhooks

You find the webhook menu under Settings.



When you create or edit a webhook, this page will occur.



1. The name is a public name that you add to the hook, used in the list of hooks, so you can identify the hook.
2. A email to a technical contact for the webhook.
3. Callback URL
Here you add your URL to where Extensio will send the webhook
4. Secret, here you add a secret. Extensio will sign the body in the hook using SHA256 with your secret. The signed value is added in *request header 'ms-signature'*. The body should be verified before processing to avoid spam calls
5. Filter event on,
Here you can limit the hook on different warehouses. If you for example need to have a hook on available balance, and your installation in Extensio handles several warehouses. you can limit the hook to only handle balances for a specific warehouse.
6. Trigger on events.
Here you mark on which events you want the Hook to fire on.

Example

The content in *Notifications* array will be different depending on the *Action*

PurchasePartiallyDelivered:

```
{
  "Id": "6e249eebb818463086ae0dda6eeba7b2",
  "Attempt": 1,
  "Properties":
  { "NotificationId": "3b3fd4a6-36d5-46fe-8a3f-e73532529db3" }
,
  "Notifications": [
  {
    "Action": "PurchasePartiallyDelivered",
    "Details":
    { "OrderNumber": "RP-101", "Warehouse": "GreenWarehouse" }
  }
  ]
}
```

ProductCreated:

```
{
  "Id": "13f078bcbe2243dc997655ed2cbbbf7",
  "Attempt": 1,
  "Properties": {
    "NotificationId": "90c6340b-1f5c-49e0-9cee-45df5dd145c2"
  },
  "Notifications": [
  {
    "Action": "ProductCreated",
    "Details": {
      "ProductNumber": "Financial Invoice"
    }
  }
  ]
}
```

Signing

To make sure the webhook is sent by Extend it is signed. It is optional to use the signature for verification.

Body is signed using SHA256 with clientsecret. The signed value is added in header 'ms-signature'

ClientSecret:

[Home](#) / [Web hook](#)

Web hook

Web hook	
Callback url *	<input type="text" value="http://internaltestreceiver"/>
Secret	<input type="text" value="3006B6D17C2449569EA05BF58A95722DE04A8509D5104205A71565682EEF2F27"/>
Enabled	<input checked="" type="checkbox"/>

Body: the full request body

SignatureFromHeader: request header 'ms-signature'

Sample pseudo code:

```
byte[] secret = Encoding.UTF8.GetBytes(ClientSecret);
using (var hasher = new HMACSHA256(secret))
{
    byte[] data = Body.ToByteArray();
    actualHash = hasher.ComputeHash(data);
}
byte[] expectedHash = FromHex(SignatureFromHeader).ToByteArray()
if(!IsSecretEqual(expectedHash, actualHash))
{
    //process web hook
}
```

Sample

ClientSecret = secret123

Body = {'test':'test2'}

BodyAsHex = 7B2774657374273A277465737432277D

ms-signature =

sha256=25FB6994568A75CD233E04BA1C653AF1BF476041CC543AF04F82CAAC482C201A



